

ANCHOR ROD PULLING EYE ASSEMBLY

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Galvanized for corrosion protection
- ✓ High strength metal

Attach guy wire to ground anchors safely.

Slingco's Anchor Rod Pulling Eye is used to position anchor correctly using Slingco's hoist when connecting guy wire.

The Slingco anchor rod pulling eye installs on 0.5" to 1.25" anchor rods and is used in conjunction with hoist to tension and install pole guy wires.

Slingco Part No.	Capacity	Working Load Limit	Height	Width	Length	Weight
SAE12540	1/2" to 1.25" Anchor Rods	6,000 lbs (2,700 kg)	5 in (125 mm)	2.6 in (65 mm)	6.25 in (159 mm)	5.3 lbs (2.4 kgs)

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478