

BLANKET MAGNET

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Hold insulating blankets in place
- ✓ Easily insert through blanket eyelets
- ✓ Hotstick moveable

The Slingco Blanket Magnet is designed to fit through the eyelets of an insulated blanket. Afterwards, the magnet along with the blanket can be placed over energized areas of transformers, switchboards and substations.

The Slingco Blanket Magnet is constructed of ultraviolet-stabilized fiberglass reinforced polymer. This reinforced polymer remains strong and resists breakage, providing a long life for the tool.

Can be placed and repositioned with hot line tools.

Slingco Part No.	Height in (mm)	Diameter in (mm)	Weight lb (g)	Magnet rating lb (kg)
PPE10785	2.4 (60.6)	1.75 (44.4)	0.2 (90.7)	120 (54.4)

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478