

DUST TIGHT



KEY FEATURES

- ✓ Provide bend support and cable pull-out resistance
- ✓ Sized to fit standard NPT connections and knockouts

Dust-Tight Cord Grips provide strain relief and bend support for cables running into machinery and connection boxes. These are sized to fit standard NPT connections from ½" to 2.5" NPT. Can also be installed in standard enclosure knockouts. These grips are made of galvanized wire mesh and provide bend support and cable pull-out resistance. The insulated versions come with installed synthetic cap for added protection from particle egress.

Slingco Part No. (Insulated)	Slingco Part No. (Non-insulated)	Range (mm)	Range (in)	NPT Size (in)
ZCS7674	ZCS7756	5.6 - 8.1	0.22 - 0.32	0.5
ZCS7675	ZCS7757	7.6 - 10.9	0.30 - 0.43	0.5
ZCS7676	ZCS7758	10.1 - 13.7	0.40 - 0.54	0.5
ZCS7677	ZCS7759	13.2 - 18.5	0.52 - 0.73	0.75
ZCS7678	ZCS7760	17.8 - 24.6	0.70 - 0.97	1
ZCS7679	ZCS7761	23.8 - 31.8	0.94 - 1.25	1.25
ZCS7680		30.5 - 38.1	1.20 - 1.50	1.5
ZCS7681		38.1 - 44.5	1.40 - 1.75	2
ZCS7682		41.1 - 50.8	1.62 - 2.00	2.5
ZCS7683		50.8 - 62.2	2.00 - 2.45	2.5

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com