

HAND LINE BLOCK (3")

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ 3" nylon fiberglass block with 1,000 lb Safe Working Load limit
- ✓ Side opening feature allows quick access to remove the hand line

Slingco's Hand Line Blocks feature a 3" nylon fiberglass block, with a safe working load limit of 1,000 lb.

Our 3" Hand Line Blocks sheave can accommodate a 5/8" diameter rope, and operates smoothly on the 1/2" diameter axle and swivel bearings. The side opening feature allows quick access to remove the hand line.

Slingco Part No.	Description	Working Load Limit (kg)	Working Load Limit (lb)
ZAB8725	3" Hand Line Block (Screw Pin)	453.59	1,000
ZAB8725-P	3" Hand Line Block (Push Pin)	453.59	1,000
ZAB8725-M	3" Hand Line Block (with Meat Hook)	453.59	1,000

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478