

# JUMPERING

## WARNING

Cancer and Reproductive Harm: [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)



## KEY FEATURES

- ✓ Lightweight and impact resistant
- ✓ Transparent clamp body for easy inspection of cable, ferrule and clamp
- ✓ Copper-based alloy clamp and floating ring contact
- ✓ Meet ASTM F2321 standard

35KV Jumper Clamps used as a part of jumper cable assemblies to bypass work areas when equipment is under repair or being upgraded. Slingco Jumper clamps are lightweight and impact resistant making them incredibly durable.

| Slingco Part No. | Line Range              | Max Continuous Amps | Threading              | Length (in) | Length (mm) | Weight (lbs) | Weight (kgs) |
|------------------|-------------------------|---------------------|------------------------|-------------|-------------|--------------|--------------|
| ZSC09344         | 954 MCM (0.162 - 1.25 ) | 400                 | 5/8" - 11 threads/inch | 11.5        | 292         | 2.5          | 1.15         |
| ZSC12110         | 477 MCM (0.162 - 0.9)   | 400                 | 5/8" - 11 threads/inch | 11.5        | 292         | 2.4          | 1.09         |

## Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

## Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



## GET IN TOUCH

 01706 855 558

 [sales@slingco.com](mailto:sales@slingco.com)

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558  
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478