

# CABLE PROTECTOR - MANUAL INSTALLATION KIT

## **WARNING**

Cancer and Reproductive Harm: [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)



## KEY FEATURES

- ✓ Calibrated for Slingco Cable Protectors
- ✓ Able to be used for installation of most stamped cable protectors in the market

Slingco's line of Cable Protectors provide a safe, quick and efficient way of conveying and securing downhole cables

into well-bores. They are ideal for the protection of any size ESP cables, control lines, umbilical cables and encapsulated bundles in well-bores.

Eliminating compression-induced damage to downhole cables, its slip and rotation resistant design is streamlined to help prevent hang-ups downhole. The tapered pins that lock the protectors to the conduit are essential to the protection of vital cables.

Slingco's Cable Protector Installation Tool Kits allow you to safely and efficiently install Slingco protectors.

Tool kits are also available in [hydraulic configurations](#).

| Description                  | Slingco Part No. |
|------------------------------|------------------|
| Manual Installation Tool Kit | ZCP4428          |

| Part Description               | Quantity |
|--------------------------------|----------|
| Manual Clamping Tool           | 1        |
| Manual Installation Tool Punch | 1        |
| Manual Installation Hammer     | 1        |

## Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

## Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



## GET IN TOUCH

 01706 855 558

 [sales@slingco.com](mailto:sales@slingco.com)

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558  
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478