

CROSS COUPLING PROTECTORS

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Various cable configuration options available
- ✓ Standard and low profile models
- ✓ Easy installation
- ✓ Securely holds and protects lines
- ✓ Special and custom features available

Slingco Cross Coupling Protectors are available in a variety of materials and configurations to protect cables and capillary tubing traveling down-hole. Customized variations allow for any cable/cap string configuration needed. Low Carbon Steel, various Stainless Steel, Inconel, Monel and other materials options available to match the requirements of your well composition. [Contact Slingco](#) for guidance on selecting the proper protector for your well.

[Download our guide: Choosing the right Cable Protector.](#)

Tubing Size	1st Cable	2nd Cable	3rd Cable	Material
2 3/8" to 13 3/8"	Various Round or Flat	Various Round or Flat	Various Round or Flat	Low Carbon Steel Zinc Passivated
2 3/8" to 13 3/8"	Various Round or Flat	Various Round or Flat	Various Round or Flat	304 SS
2 3/8" to 13 3/8"	Various Round or Flat	Various Round or Flat	Various Round or Flat	316 SS
2 3/8" to 13 3/8"	Various Round or Flat	Various Round or Flat	Various Round or Flat	410 SS
2 3/8" to 13 3/8"	Various Round or Flat	Various Round or Flat	Various Round or Flat	1Cr13
2 3/8" to 9 7/8"	Various Round or Flat	Various Round or Flat	Various Round or Flat	Inconel
2 3/8" to 9 7/8"	Various Round or Flat	Various Round or Flat	Various Round or Flat	Monel

Contact Slingco to receive drawing of specific configurations

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478