

DELUXE CORD SOCKS



KEY FEATURES

- ✓ Available with straight male, 90 degree male, 45 degree male and straight female connections.
- ✓ Provide bend support and pull out resistance
- ✓ Aluminium Barrel & Stainless Steel wire mesh

Deluxe Cord Socks provide strain relief and bend support for cables running into machinery and connection boxes. Select the deluxe grip that fits the NPT size being connected to. Available with Straight Male, 90 degree Male, 45 degree Male and Straight Female connections. The Stainless Steel wire mesh sock is sized to provide bend support and pull out resistance for the cable range listed.

3/8" NPT

Range (in)	Range (mm)	Straight Male
0.19 - 0.25	4.8 - 6.4	ZCS7713
0.25 - 0.31	6.4 - 7.9	ZCS7714
0.31 - 0.38	7.9 - 10	ZCS7715
0.38 - 0.44	10 - 11.1	ZCS7716

1/2" NPT

Range (in)	Range (mm)	Straight Male	90° Male	Straight Female
0.19 - 0.25	4.8 - 6.4	ZCS7721	ZCS7727	ZCS7735
0.25 - 0.38	6.4 - 10	ZCS7722	ZCS7728	ZCS7736
0.38 - 0.50	10 - 12.7	ZCS7723	ZCS7729	ZCS7737
0.50 - 0.63	12.7 - 16	ZCS7724	ZCS7730	ZCS7738
0.63 - 0.75	16 - 19	ZCS7725		
0.75 - 0.88	19 - 22.4	ZCS7726		

3/4" NPT

Range (in)	Range (mm)	Straight Male	90° Male	Straight Female
0.25 - 0.38	6.4 - 10	ZCS7739	ZCS7744	ZCS7752
0.38 - 0.50	10 - 12.7	ZCS7740	ZCS7745	ZCS7753
0.50 - 0.63	12.7 - 16	ZCS7741	ZCS7746	ZCS7754
0.63 - 0.75	16 - 19	ZCS7742	ZCS7747	ZCS7755
0.75 - 0.88	19 - 22.4	ZCS7743		



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

DELUXE CORD SOCKS

1" NPT

Range (in)	Range (mm)	Straight Male	90° Male	Straight Female
0.44 - 0.56	11.2 - 14	ZCS7887	ZCS7894	ZCS7904
0.56 - 0.69	14 - 17.5	ZCS7888	ZCS7895	ZCS7905
0.63 - 0.75	16 - 19	ZCS7889	ZCS7896	ZCS7906
0.75 - 0.88	19 - 22.4	ZCS7890	ZCS7897	ZCS7907
0.88 - 1.00	22.4 - 25.4	ZCS7891	ZCS7898	ZCS7908
1.00 - 1.13	25.4 - 28.7	ZCS7892		
1.13 - 1.25	28.7 - 31.8	ZCS7893		

1.25" NPT

Range (in)	Range (mm)	Straight Male	90° Male
0.75 - 0.88	19 - 22.4	ZCS7909	ZCS7914
0.88 - 1.00	22.4 - 25.4	ZCS7910	ZCS7915
1.00 - 1.13	25.4 - 28.7	ZCS7911	ZCS7916
1.13 - 1.25	28.7 - 31.8	ZCS7912	ZCS7917
1.25 - 1.38	31.8 - 35.1	ZCS7913	ZCS7918

1.5" NPT

Range (in)	Range (mm)	Straight Male	90° Male
0.75 - 0.88	19 - 22.4	ZCS7919	ZCS7929
0.88 - 1.00	22.4 - 25.4	ZCS7920	ZCS7930
1.00 - 1.13	25.4 - 28.7	ZCS7921	ZCS7931
1.13 - 1.25	28.7 - 31.8	ZCS7922	ZCS7932
1.25 - 1.38	31.8 - 35.1	ZCS7923	ZCS7933
1.31 - 1.44	33.3 - 36.6	ZCS7924	
1.44 - 1.56	36.6 - 39.6	ZCS7925	
1.56 - 1.69	39.6 - 43	ZCS7926	
1.69 - 1.81	43 - 46	ZCS7927	
1.75 - 1.88	44.5 - 47.8	ZCS7928	

2" NPT

Range (in)	Range (mm)	Straight Male	90° Male
1.25 - 1.38	31.8 - 35.1	ZCS7934	ZCS7945
1.31 - 1.44	33.3 - 36.6	ZCS7935	ZCS7946
1.44 - 1.56	36.6 - 39.6	ZCS7936	ZCS7947
1.56 - 1.69	39.6 - 43	ZCS7937	ZCS7948
1.69 - 1.81	43 - 46	ZCS7938	ZCS7949
1.75 - 1.88	44.5 - 47.8	ZCS7939	ZCS7950
1.81 - 1.94	46 - 49.3	ZCS7940	
1.94 - 2.06	49.3 - 52.3	ZCS7941	
2.06 - 2.19	52.3 - 55.5	ZCS7942	
2.19 - 2.31	55.5 - 58.7	ZCS7943	
2.31 - 2.44	58.7 - 61.9	ZCS7944	



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

DELUXE CORD SOCKS

2.5" NPT

Range (in)	Range (mm)	Straight Male
1.69 - 1.81	43 - 46	ZCS7951
1.81 - 1.94	46 - 49.3	ZCS7952
1.94 - 2.06	49.3 - 52.3	ZCS7953
2.06 - 2.19	52.3 - 55.5	ZCS7954
2.19 - 2.31	55.5 - 58.7	ZCS7955
2.31 - 2.44	58.7 - 62	ZCS7956

3.0" NPT

Range (in)	Range (mm)	Straight Male
1.69 - 1.81	43 - 46	ZCS7957
1.81 - 1.94	46 - 49.3	ZCS7958
1.94 - 2.06	49.3 - 52.3	ZCS7959
2.06 - 2.19	52.3 - 55.5	ZCS7960
2.19 - 2.31	55.5 - 58.7	ZCS7961
2.31 - 2.44	58.7 - 62	ZCS7962
2.44 - 2.63	62 - 66.5	ZCS7963
2.63 - 2.81	66.5 - 71.4	ZCS7964
2.81 - 3.00	71.4 - 76.2	ZCS7965
3.00 - 3.25	76.2 - 82.6	ZCS7966

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com