

# TRIPLEX DISPENSER

## WARNING

Cancer and Reproductive Harm: [www.p65warnings.ca.gov](http://www.p65warnings.ca.gov)



## KEY FEATURES

- ✓ Adjustable Break Tension
- ✓ Variable arm settings to match coil sizes

The Slingco Triplex dispenser is designed to be permanently mounted for the efficient dispensing of triplex. Slingco's triplex dispenser is designed to keep linemen safe while saving time and effort.

Constructed of high strength steel coated in a durable black finish allows the unit to endure the harsh outdoor environments. The high load sealed ball bearing keeps operation and rotation smooth.

Easily adjust break tension with a 3/4" wrench. Simple pull knob operation for loading of triplex coils.

Wire guide allows easy payout and rewinding of triplex.

| Slingco Part No. | Coil OUTSIDE Diameter Range (mm) | Coil OUTSIDE Diameter Range (in) | Coil INSIDE Diameter Range (cm) | Coil INSIDE Diameter Range (in) | Coil Width Capacity (cm) | Coil Width Capacity (in) | Weight (kg) | Weight (lb) |
|------------------|----------------------------------|----------------------------------|---------------------------------|---------------------------------|--------------------------|--------------------------|-------------|-------------|
| ZWM09903         | 66 - 81.3                        | 26 - 32                          | 35.5 - 50.8                     | 14 - 20                         | 26                       | 10.25                    | 24.5        | 54          |

## Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

## Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



## GET IN TOUCH

 01706 855 558

 [sales@slingco.com](mailto:sales@slingco.com)

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558  
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478