

ULTRA-FLEX NON-METALLIC PULLING SOCK

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Non-Metallic
- ✓ Light weight yet strong
- ✓ Nylon collar
- ✓ Colored tabs for easy identification

Lightweight and strong pulling sock made of non-metallic aramid fibre.

Part No.	Range (mm)	Range (in)	Colour Code	Color Code	Approx. Break Load (kg)	Approx. Break Load (lbs.)
ZCS09336	16 - 19	0.63 - 0.75	Yellow	Yellow	2,267	5,000
ZCS09337	19 - 25	0.75 - 1.0	Red	Red	2,721	6,000
ZCS09338	25 - 32	1.0 - 1.25	Blue	Blue	2,721	6,000
ZCS09339	32 - 38	1.25 - 1.50	White	White	2,721	6,000

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478