

UNIVERSAL EYE CLOSED MESH CABLE SUPPORT SOCKS

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed with adjustable universal eye

Fitted with an adjustable eye for easy and secure attachment, where the end of the cable can be inserted in to the support sock. Made from 304 Stainless Steel.

Slingco Part No.	Approx. Break Load (kg)	Approx. Break Load (lb)	Lattice Length (mm)	Lattice Length (in)	Range (mm)	Range (in)
ZCS2664	240	530	254	10	12 - 16	0.50 - 0.63
ZCS2665	360	790	254	10	16 - 19	0.63 - 0.75
ZCS2666	460	1,020	330	13	19 - 25	0.75 - 1.00
ZCS2667	730	1,610	355	14	25 - 31	1.00 - 1.25
ZCS2324	730	1,610	381	15	31 - 38	1.25 - 1.50
ZCS2668	730	1,610	432	17	38 - 44	1.50 - 1.75
ZCS2669	975	2,150	483	19	44 - 50	1.75 - 2.00
ZCS2670	1,480	3,260	533	21	50 - 63	2.00 - 2.50
ZCS2671	1,480	3,260	584	23	63 - 76	2.50 - 3.00

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478