

DOUBLE EYE CLOSED MESH CABLE SUPPORT GRIPS

⚠ WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed for 2 connect/support points

Double eye closed mesh support grip in 304 stainless steel. Two eyes for two connect/support points. Closed mesh for when end of cable is available.

Slingco Part No.	Approx. Break Load (kg)	Approx. Break Load (lb)	Lattice Length (mm)	Lattice Length (in)	Lattice Material	Range (mm)	Range (in)
ZCS2038	230	512	247	9.7	304 Stainless	12 - 16	0.50 - 0.63
ZCS2039	335	740	247	9.7	304 Stainless	16 - 19	0.63 - 0.75
ZCS2040	450	1,000	331	13	304 Stainless	19 - 25	0.75 - 1.00
ZCS2041	695	1,540	344	15	304 Stainless	25 - 31	1.00 - 1.25
ZCS2042	695	1,540	382	16.5	304 Stainless	31 - 38	1.25 - 1.50
ZCS2043	910	2,010	420	15	304 Stainless	38 - 44	1.50 - 1.75
ZCS2044	1,465	2,300	509	21	304 Stainless	44 - 50	1.75 - 2.00
ZCS2045	1,465	3,230	535	24	304 Stainless	50 - 63	2.00 - 2.50
ZCS2046	1,815	4,000	611	26	304 Stainless	63 - 76	2.50 - 3.00
ZCS2047	1,815	4,000	662	29	304 Stainless	76 - 89	3.00 - 3.50
ZCS2048	1,815	4,000	738	29	304 Stainless	89 - 102	3.50 - 4.00
ZCS6404	1,815	4,000	762	30	304 Stainless	102 - 114	4.00 - 4.50
ZCS6405	1,815	4,000	762	30	304 Stainless	114 - 127	4.50 - 5.00
ZCS6406	1,815	4,000	762	30	304 Stainless	127 - 140	5.00 - 5.50

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478