

DOUBLE EYE MARINE GRIPS

⚠ WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Bespoke design available
- ✓ Single, double, triple and quadruple weave depending upon requirement
- ✓ Thimble eye optional

These speciality grips, often called chinese fingers, are extremely heavy duty and suitable for large underwater pulling applications, plus others within the oil and gas industry. Galvanised steel construction for heavy duty pulling such as array cable, export cable, umbilicals and other underwater cable installations. Sizes handle cable ranging from 100mm to over 550mm diameter. Manufactured to order.

Slingco Part No. FLEX Eye	Slingco Part No. THIMBLE Eye	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Lattice Material	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS12754-2M	ZCS12754-THI-2M	90 - 125	3.5 - 5	2,000	78.75	Galv.	55,000	121,250
ZCS12754-2.5M	ZCS12754-THI-2.5M	90 - 125	3.5 - 5	2,500	98.5	Galv.	55,000	121,250
ZCS12754-3M	ZCS12754-THI-3M	90 - 125	3.5 - 5	3,000	118	Galv.	55,000	121,250
ZCS3535	ZCS3535-THI	102 - 127	4 - 5	2,005	78.75	Galv.	56,500	124,560
ZCS12755-2.5M	ZCS12755-THI-2.5M	110 - 145	4.3 - 5.7	2,500	98.5	Galv.	60,000	132,275
ZCS12755-3M	ZCS12755-THI-3M	110 - 145	4.3 - 5.7	3,000	118	Galv.	60,000	132,275
ZCS3536	ZCS3536-THI	127 - 152	5 - 6	1,821	71.7	Galv.	56,500	124,560
ZCS12756	ZCS12756-THI	130 - 172	5.1 - 6.7	3,000	118	Galv.	75,000	165,350
ZCS3537	ZCS3537-THI	152 - 203	6 - 8	1,633	64.3	Galv.	57,500	126,765
ZCS12757	ZCS12757-THI	155 - 210	6.1 - 8.25	3,000	118	Galv.	80,000	176,370
ZCS12758	ZCS12758-THI	195 - 250	7.67 - 9.8	3,000	118	Galv.	90,000	198,400
ZCS3538	ZCS3538-THI	203 - 255	8 - 10	2,047	80.5	Galv.	71,000	156,528
ZCS12759	ZCS12759-THI	235 - 285	9.25 - 11.22	3,000	118	Galv.	95,000	209,439
ZCS3539	ZCS3539-THI	255 - 305	10 - 12	1,945	76.5	Galv.	71,000	156,528
ZCS3540	ZCS3540-THI	305 - 355	12 - 14	2,460	97	Galv.	71,000	156,528
ZCS3540-3M	ZCS3540-THI-3M	305 - 355	12 - 14	3,000	118	Galv.	71,000	156,528

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478

DOUBLE EYE MARINE GRIPS

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478