

DOUBLE EYE SPLIT MESH LACE CLOSING SUPPORT GRIPS

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed for 2 connect/support points
- ✓ Use when the end of the cable is not accessible

Double eye split mesh lace closing, in 304 Stainless Steel, for secure attachment and support where the cable end is not accessible.

Slingco Part No.	Approx. Break Load (kg)	Approx. Break Load (lb)	Lattice Length (mm)	Lattice Length (in)	Lattice Material	Range (mm)	Range (in)
ZCS2998	240	530	254	10	304 Stainless	12 - 16	0.50 - 0.63
ZCS2999	360	790	254	10	304 Stainless	16 - 19	0.63 - .0.75
ZCS3000	460	1,020	330	13	304 Stainless	19 - 25	0.75 - 1.00
ZCS3001	730	1,610	355	14	304 Stainless	25 - 31	1.00 - 1.25
ZCS3002	730	1,610	381	15	304 Stainless	31 - 38	1.25 - 1.50
ZCS3003	730	1,610	432	17	304 Stainless	38- -44	1.50 - 1.75
ZCS3004	975	2,150	482	19	304 Stainless	44 - 50	1.75 - 2.00
ZCS3005	1,480	3,260	533	21	304 Stainless	50 - 63	2.00 - 2.50
ZCS3006	1,480	3,260	584	23	304 Stainless	63 - 76	2.50 - 3.00
ZCS3007	2,222	4,900	635	25	304 Stainless	76 - 89	3.00 - 3.50
ZCS3008	2,222	4,900	685	27	304 Stainless	89 - 102	3.50 - 4.00

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478