

NS – NON-METALLIC (ARAMID) SINGLE EYE CABLE GRIP

⚠ WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Continuous weave configuration
- ✓ No fraying wires
- ✓ Lighter and safer to handle
- ✓ Longer Life

Ideal for fibre optic applications, offshore or for a multitude of uses in the electrical industry; dramatically improved weight to break ratio. Slingco's non-metallic pulling grips are made of a high-strength, non-metallic aramid fibre, with UV protective coating; they are suitable for pulling both single cable and cable bundles. These woven mesh grips offer a non-metallic alternative to steel. Non-metallic material is easy to work with even without gloves.

Single Eye Single Weave Non-Metallic Grip

Slingco Part No.	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS1040	10 - 20	0.38 - 0.75	552	21	1,115	2,460
ZCS1022	20 - 30	0.75 - 1.25	523	21	1,620	3,580
ZCS2923	25 - 38	1.00 - 1.50	573	23	1,620	3,580
ZCS1041	30 - 40	1.25 - 1.50	642	25	2,230	4,920
ZCS1042	40 - 50	1.50 - 2.00	485	19	2,640	5,820

Single Eye Double Weave Non-Metallic Grip

Slingco Part No.	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS1023	30 - 40	1.25 - 1.50	642	25	4,470	9,860
ZCS1024	40 - 50	1.50 - 2.00	523	21	5,390	11,880
ZCS1179	50 - 65	2.00 - 2.50	636	25	7,210	15,900
ZCS1180	65 - 76	2.50 - 3.00	908	36	7,210	15,900
ZCS1181	76 - 102	3.00 - 4.00	1,029	40	7,210	15,900
ZCS4079	100 - 125		3,168		7,210	

Single Eye Double Weave High Strength Non-Metallic Grip

Slingco Part No.	Range (in)	Lattice Length (in)	Approx. Break Load (lb)
ZCS13054	4.00 - 5.00	118	45,500

Dimensions



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478

NS – NON-METALLIC (ARAMID) SINGLE EYE CABLE GRIP

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478