

RT TYPE - ROTATING EYE DOUBLE WEAVE CABLE GRIPS

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Double weave construction
- ✓ Increased pulling strength
- ✓ Protective shoulders to prevent abrasion
- ✓ Rotating eye to easy match with line swivel

Double weave construction for medium to heavy pulling applications in underground installations. Additionally its steel forged revolving head is ideal for connecting to Slingco swivels.

Warning: The Slingco RT Type Rotating Eye Grip does not revolve under load. The rotating eye does not replace the need for a swivel.

Short Length - Galvanised Steel

Slingco Part No.	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS2734	13 - 16	0.50 - 0.62	300	12	2,540	5,600
ZCS2735	16 - 19	0.62 - 0.75	305	12	3,084	6,800
ZCS2736	19 - 25	0.75 - 1.00	474	18.5	3,084	6,800
ZCS2738	25 - 38	1.00 - 1.50	549	21.5	5,806	12,800
ZCS2739	38 - 50	1.50 - 2.00	552	22	7,440	16,400
ZCS2740	50 - 63	2.00 - 2.50	587	23	12,338	27,200
ZCS2741	63 - 76	2.50 - 3.00	642	25	14,969	33,000
ZCS2742	76 - 89	3.00 - 3.50	731	29	19,504	41,000
ZCS2743	89 - 102	3.50 - 4.00	804	32	19,504	43,000



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478

RT TYPE - ROTATING EYE DOUBLE WEAVE CABLE GRIPS

Standard - Longer Length - Galvanised Steel

Slingco Part No.	Range (mm)	Range (in)	Lattice Length (mm)	Lattice Length (in)	Approx. Break Load (kg)	Approx. Break Load (lb)
ZCS2745	13 - 16	0.50 - 0.62	405	16	2,540	5,600
ZCS2746	16 - 19	0.62 - 0.75	436	17	3,084	6,800
ZCS2747	19 - 25	0.75 - 1.00	765	30	3,084	6,800
ZCS2748	25 - 38	1.00 - 1.50	812	32	5,806	12,800
ZCS2749	38 - 50	1.50 - 2.00	747	30	7,439	16,400
ZCS2750	50 - 63	2.00 - 2.50	740	29	12,338	27,200
ZCS2751	63 - 76	2.50 - 3.00	893	35	14,969	33,000
ZCS2752	76 - 89	3.00 - 3.50	1,005	40	18,597	41,000
ZCS2753	89 - 102	3.50 - 4.00	1,014	40	19,504	43,000
ZCS2754	102 - 115	4.00 - 4.50	947	37.5	19,504	43,000
ZCS2755	115 - 127	4.50 - 5.00	1,350	53	19,504	43,000
ZCS2756	127 - 153	5.00 - 6.00	1,361	54	21,772	48,000
ZCS2757	153 - 178	6.00 - 7.00	1,563	62	19,504	43,000

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478