

SINGLE EYE SPLIT MESH LACE CLOSING SUPPORT GRIPS

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Made from 304 stainless steel
- ✓ Designed for use when the end of the cable is not accessible

In 304 stainless steel. Split mesh is for when end of cable is not available.

Slingco Part No.	Approx. Break Load (kg)	Approx. Break Load (lb)	Lattice Length (mm)	Lattice Length (in)	Range (mm)	Range (in)
ZCS1904	255	567	247	9.7	12 - 16	0.50 - 0.63
ZCS1905	358	890	247	9.7	16 - 19	0.63 - .0.75
ZCS1906	470	1,040	331	13	19 - 25	0.75 - 1.00
ZCS1907	770	1,700	344	13.5	25 - 31	1.00 - 1.25
ZCS1908	770	1,700	382	15	31 - 38	1.25 - 1.50
ZCS1909	770	1,700	420	16.5	38- -44	1.50 - 1.75
ZCS1910	1,040	2,300	509	20	44 - 50	1.75 - 2.00
ZCS1911	1,540	3,400	535	21	50 - 63	2.00 - 2.50
ZCS1912	1,540	3,400	611	24	63 - 76	2.50 - 3.00
ZCS1913	2,265	5,000	662	26	76 - 89	3.00 - 3.50
ZCS1914	2,265	5,000	738	29	89 - 102	3.50 - 4.00

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478