

STANDARD DUTY HOSE RESTRAINT GRIPS

WARNING

Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Prevent whipping in the event of a pressurised hose becoming detached from its fitting
- ✓ Made from the highest grade galvanised steel and 316 stainless steel wire
- ✓ Colour coded for easy range identification

Slingco offer a range of safety restraining grips and whipchecks designed to prevent whipping in the event of a pressurised hose becoming detached from its fitting.

Made from the highest grade galvanised steel and 316 stainless steel wire, and colour coded for range identification, our grips are designed for various plant-critical applications across a wide range of commercial industries. Suitable for restraining all types of high pressure hoses such as water and air hoses, hydraulic hoses, concrete pump and delivery hoses as well as supporting electrical cabling within critical applications within mining, automation and other industrial sectors.

The grips are woven in such a way that the lattice or weave is uniform throughout its length, ensuring even load protection around the hose. This helps with any adverse abrasion to the hose and prevents displacement in the event of rupture. Available for 5mm to 200mm diameter hoses.



GET IN TOUCH

 01706 855 558

 sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478

STANDARD DUTY HOSE RESTRAINT GRIPS

Standard Duty Hose Restraints

Slingco Part No.	Sock Material	Thimble Eye	Thimble Size	Weave	Range (mm)	Range (in)	Eye Length (mm)	Eye Length (in)	Lattice/Weave (mm)	Lattice/Weave (in)	Overall length (mm)	Overall Length (in)
ZCS14350	Galv	SS	6	Double	6-14	0.24-0.55	90	4	330	13	420	17
ZCS14351	Galv	SS	6	Double	14-20	0.55-0.80	90	4	352	14	442	17
ZCS14352	Galv	SS	6	Double	20-30	0.80-1.25	115	5	574	23	689	27
ZCS14353	Galv	SS	8	Double	30-40	1.25-1.50	165	6	810	32	975	38
ZCS14354	Galv	SS	8	Double	40-50	1.50-2.00	185	7	893	35	1078	42
ZCS14355	Galv	SS	10	Double	50-60	2.00-2.40	230	9	1215	48	1445	57
ZCS14356	Galv	SS	10	Double	60-70	2.40-2.75	240	9	1224	48	1464	58
ZCS14357	Galv	SS	10	Double	70-90	2.75-3.50	260	10	1295	51	1555	61
ZCS14358	Galv	SS	14	Double	90-110	3.50-4.30	280	11	1468	58	1748	69
ZCS14359	Galv	SS	14	Double	110-130	4.30-5.00	350	14	1551	61	1901	75
ZCS14360	Galv	SS	16	Double	120-150	4.70-5.90	400	16	1582	62	1982	78
ZCS14361	Galv	SS	16	Double	140-180	5.50-7.00	450	18	1533	60	1983	78
ZCS14362	SS	SS	6	Double	6-14	0.24-0.55	90	4	330	13	420	17
ZCS14363	SS	SS	6	Double	14-20	0.55-0.80	90	4	352	14	442	17
ZCS14364	SS	SS	6	Double	20-30	0.80-1.25	115	5	574	23	689	27
ZCS14365	SS	SS	8	Double	30-40	1.25-1.50	165	6	810	32	975	38
ZCS14366	SS	SS	8	Double	40-50	1.50-2.00	185	7	893	35	1078	42
ZCS14367	SS	SS	10	Double	50-60	2.00-2.40	230	9	1215	48	1445	57
ZCS14368	SS	SS	10	Double	60-70	2.40-2.75	240	9	1224	48	1464	58
ZCS14369	SS	SS	10	Double	70-90	2.75-3.50	260	10	1295	51	1555	61
ZCS14370	SS	SS	14	Double	90-110	3.50-4.30	280	11	1468	58	1748	69

(continued)

Slingco Part No.	Break load (kg)	Break Load (lb)	Break load (kN)	Colour code	Color code
ZCS14350	1600	3,527	16	White	White
ZCS14351	2000	4,409	20	White	White
ZCS14352	2500	5,512	25	White	White
ZCS14353	4300	9,480	42	Brown	Brown
ZCS14354	6200	13,669	61	Orange	Orange
ZCS14355	8100	17,857	79	Yellow	Yellow
ZCS14356	8100	17,857	79	Blue	Blue
ZCS14357	8100	17,857	79	Red	Red
ZCS14358	10500	23,148	103	Green	Green
ZCS14359	12500	27,558	123	Black	Black
ZCS14360	16000	35,274	157	Grey	Grey
ZCS14361	20000	44,092	196	Light Blue	Light Blue
ZCS14362	1280	2,822	13	White	White
ZCS14363	1600	3,527	16	White	White
ZCS14364	2000	4,409	20	White	White
ZCS14365	3440	7,584	34	Brown	Brown
ZCS14366	4960	10,935	49	Orange	Orange
ZCS14367	6480	14,286	64	Yellow	Yellow
ZCS14368	6480	14,286	64	Blue	Blue
ZCS14369	6480	14,286	64	Red	Red
ZCS14370	8400	18,519	82	Green	Green



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478

STANDARD DUTY HOSE RESTRAINT GRIPS

Wide-Range Restraint

Slingco Part No.	Sock Material	Thimble Eye	Thimble Size	Weave	Range (mm)	Range (in)	Eye Length (mm)	Eye Length (in)	Lattice/Weave (mm)	Lattice/Weave (in)	Overall length (mm)	Overall Length (in)
ZCS14347	Galv	N/A	N/A	Double	50-120	2.00-4.72	306	12	594	23.4	900	900

(continued)

Slingco Part No.	Break load (kg)	Break Load (lb)	Break load (kN)	Colour code	Color code
ZCS14347	5080	11,200	50	ZCS14347	-

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/- 10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com