

Y TYPE

⚠ WARNING


Cancer and Reproductive Harm: www.p65warnings.ca.gov



KEY FEATURES

- ✓ Prevents whipping from detached pressure hoses
- ✓ Threaded bolt fitting
- ✓ Made from 316 Stainless steel

Y Type Threaded Bolt Hose Grip - 316 Stainless Steel



Slingco Part No.	Approx. Break Load (kg)	Approx. Break Load (lb)	B (mm)	B (in)	C (mm)	C (in)	D (mm)	D (in)	Ø A mean (mm)	Ø A mean (in)	Ø E (mm)	Ø E (in)	Range (mm)	Range (in)
ZCS5422	1,161	2,600	1,041	41.0	737	29.0	305	12.0	9.5	0.37	18 TPI	5/16 BSW	6 - 13	0.25 - 0.5
ZCS5423	1,562	3,500	991	39.0	686	27.0	305	12.0	16	0.62	18 TPI	5/16 BSW	13 - 19	0.5 - 0.75
ZCS5424	5,357	12,000	1,092	43.0	787	31.0	305	12.0	32	1.25	12 TPI	1/2 BSW	25 - 38	1.0 - 1.5



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Y TYPE

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-10%. Please contact us if you have any questions.

Range dimension overlaps

If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.



GET IN TOUCH

☎ 01706 855 558

✉ sales@slingco.com

Slingco Ltd, Gateway Business Park, New Hall Hey Road, Rawtenstall, BB4 6JG t: 01706 855558
Slingco America Inc, 3100 Jonquil Drive SE, Smyrna, Georgia, 30080, USA t: 888 685 9478